


PUREXCHANGE

Cabinet Series



The PureXchange Cabinet Series is a cutting-edge water softener designed to elevate your water quality. With a service flow rate of up to 26 gallons per minute (gpm), it ensures a constant supply of softened water for your entire home. Optimize the regeneration process by using a down-flow brine cycle with a double backwash feature to enhancing its cleansing capability. You can customize its regeneration frequency with the day override feature.

With a nonvolatile memory for operational data storage, it delivers consistent performance with minimal hassle. The PureXchange also features treated water regenerate refill and floating reserve for efficient water usage monitoring. Using FDA grade certified high capacity resin and components that are WQA certified, it guarantees reliable and exceptional water softening for your household.




Warranty

Industry leading limited 10 year warranty on core components. Including a comprehensive 2 year warranty on all moving parts.



High-Speed Performance

With a service flow rate of up to 26gpm, enjoy a steady and efficient supply of purified water throughout your home.



Efficiency & Control

Benefit from versatile features like the days override function and a floating reserve that optimizes water and salt usage.

Specification Sheet

GENERAL

Inlet/Outlet Fittings 3/4" to 1.5" NPS
Cycles Up to 6
Valve Material Noryl (1) or Equivalent
Regeneration Up-flow

TANK APPLICATIONS

Water Softener 6" – 13" Diameter

OPERATING PRESSURES

Minimum/Maximum 20 psi – 90 psi

OPERATING TEMPERATURES

Minimum/Maximum 40° – 100° F

CYCLES OF OPERATION

1. Backwash 1st (upflow) 1 – 95 min
2. Regenerate Draw/Slow Rinse (downflow) 1 – 180 min
3. Backwash 2nd (upflow) 1 – 95 min
4. Fast Rinse (downflow) 1 – 95 min
5. 5. Regenerate Refill (in service with treated water) 0.1 – 99.0 or off
6. 6. Service (downflow)

System	Tank Size	Flow Rate	Weight	Height	Width	Inlet/Outlet
32k	10 x 35	14 gpm	98 lbs	45"	14"	1"
48k	12 x 35	17 gpm	124 lbs	45"	14"	1"